

# **PROFIVE 2290 5W-30**

## Synthetic oil.

A Low-SAPS technology lubricant specially developed to meet standard PSA B71 2290 (version 2017) recommended for PSA Group vehicles (Peugeot, Citroën and DS). Compatible with Euro 5 and Euro 6 diesel engines with diesel particulate filter and petrol engines with catalytic converter, with the exception of "Blue HDI" and "Puretech" engines which must use a lubricant which meets standards PSA B71 2312 or PSA B71 2010.

This technology reduces the risks associated with LSPI (Low Speed Pre-Ignition).

This lubricant meets the ACEA C2-16 specifications recommended by the following manufacturers: FIAT, IVECO, TOYOTA, HONDA, MITSUBISHI, SUBARU, SUZUKI, MAZDA Diesel from 2013.

#### PERFORMANCES

Standards : ACEA C2-16 Spécifications : Peugeot/Citroën Automobiles B71 2290-17\* Fiat 9.55535.S1 Iveco 18-1811 SC1

\* Approved quality. Use recommended under manufacturers' warranties.

### **BODIES and MANUFACTURERS – Field of application -**

**ACEA C2-16:** requiring a low-SAPS oil (low sulphated ash content <0.8%, 0.07%<Phosphorus<0.09%, S<0.3%), enabling a reduction in fuel consumption (with HTHS viscosity > 2.9 mPa.S) and achieving the maximum oil change intervals specified by the engine manufacturer.

**PSA B71 2290 -17:** Compatible with any PSA Group diesel engine (with or without DPF) and petrol engine made after 2014 with the exception of the "Blue HDI" engines for which PROFIVE CRYSTAL 0W-30 should be used which meets standard PSA B71 2312



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com



# **PROFIVE 2290 5W-30**

Caractéristiques	Normes	Unités	Valeurs
Color	-	-	Brown
Density at 20°C	NFT 60-101	g/cm3	0.845
Viscosity at 40°C	ASTM D445	mm²/s	52.5
Viscosity at 100°C	ASTM D445	mm²/s	9.8
Viscosity index	NFT 60-136	-	177
Pour point	ASTM D2602	°C	-45
Flash point	ASTM D92	°C	230
Noack	-	%	11.9

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : I-97-1901 Date of issue : 02/10/2019



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com